


SERIES FP 70/...

FOR WALLS AND FLOORS

EXPANSION JOINT SYSTEMS

- INSERT REPLACEABLE AT ANY TIME
- POSITIVE CONNECTION OF PRODUCTION LENGTHS BY STAGGERING THE JOINTS
- PERFORATED MOUNTING BRACKETS
- MOVEMENT CAPACITY 25 MM
- FOR JOINT WIDTHS UP TO 70 MM



TECHNICAL DATA

Profile	Joint width max. mm	Total movement mm	Visible width of profile mm	Total width of profile mm	Installation height mm	Load capacity private cars kN	*Load capacity lorries (DIN 1072) kN	Load capacity fork lift trucks (DIN 1055) kN
FP 70/2100	70	25 +16/-9	76	210	21	30	300	not allowed
FP 70/3000	70	25 +16/-9	76	210	30	30	300	not allowed
FP 70/4000	70	25 +16/-9	76	210	40	30	300	not allowed
FP 70/5000	70	25 +16/-9	76	210	50	30	300	not allowed
FP 70/6500	70	25 +16/-9	76	210	65	30	300	not allowed
FP 70/7500	70	25 +16/-9	76	210	75	30	300	not allowed
FP 70/8500	70	25 +16/-9	76	210	85	30	300	not allowed

Larger installation heights on request


*not designed for permanent use

MATERIAL

Aluminium side plates with perforated mounting brackets.
Flexible high quality elastomeric insert, long wearing, weather resistant, temperature resistant (-30°C to + 120°C), extensively resistant to oils, acids and bitumen.

Production length: 4 m, standard colours: black, grey
Corner versions: page 36–37, installation instructions: page 39

For installation in asphalt, please ask for our technical advice.



FP 70/3000

Scale 1 : 2